

12 REELS FOR SOLDERING WIRE, LYONESE THREAD

Recommended for soldering wire and Lyonese thread

TOLERANCES

All dimensions, weights and loads stated are approximate values; tolerances and deviations which are customary for the industry remain reserved.



MATERIAL

The material options for the reels are indicated as follows:

HIPS = high impact polystyrene

ABS = acrylonitrile-butadiene-styrene

PP = polypropylene

Various colours are available. Further details can be found in our material data sheets.

Designation	Flange Ø	Barrel Ø	Central bore Ø	Width	Winding width	Flange thickness	Winding- volume	Central bore Ø tapered part	Drive- hole/pin	Drive- distance
	d1 [mm]	d2 [mm]	d3 [mm]	L1 [mm]	L2 [mm]	S [mm]	V [cm ³]	d4 [mm]	d5 [mm]	E1 [mm]
Reel 26/2	39	21	9	44	38	3	32			
Reel 50/28-E	50	28	11	50	38	6	51	15		
Reel 108/1	50	20	16	90	80	5	132			
Reel 172/1	60	20	16	90	80	5	201			
Reel 63/37-E	63	37	11	63	49	7	100	15		
Reel 80 E	80	50	16	80	64	8	196	24	2x7	20
Reel HK 80/16-95	80	38	16	95	77	9	321			
Reel MeFo 220/4	80	37	16	90	80	5	316			
Reel 100/50-E	100	50	16	100	80	10	471	24	2x7	20
Reel ET 100-E	100	80	16	125	100	12.5	282	24	2x7	20
Reel MeFo 120	120	42	16.3	90	80	5	793			
Reel MeFo 120/21	120	42	16.3	120	82	19	787			
Reel MeFo 160	160	65	16.3	93	80	6.5	1343			

TECHNICAL DRAWING

Spools

