

15 CABLE REELS AND UTILITY REELS

KCS-spools distinguish themselves by the robust geometry of the flanges and the one-piece barrel. The material is adapted to the demanding application in changing climatic conditions.



CABLE REELS

KCS-spools distinguish themselves by the robust geometry of the flanges and the one-piece barrel. The material is adapted to the demanding application in changing climatic conditions. These characteristics are the reason for the known high life expectancy.

UTILITY REELS

The KCS utility spools are characterized by a beneficial price performance ratio. Ecological friendly regrinds protect the environment. The spools are fully reusable with no chemical impregnation or waste and disposable issues when compared to plywood reels.

Designation	Flange Ø	Barrel Ø	Central bore Ø	Width	Winding width	Flange thickness	Winding- volume	Central bore Ø tapered part	Drive- hole/pin	Drive- distance
	d1 [mm]	d2 [mm]	d3 [mm]	L1 [mm]	L2 [mm]	S [mm]	V [cm³]	d4 [mm]	d5 [mm]	E1 [mm]
Reel HS 150 / 150/60-76	150	65	60	76	70	3	1004			
Reel HS 151 /0150/60-166	150	65	60	166	160	3	2296			
Reel HS 200 /195/60-250	195	100	60	250	210	20	4622		2x13	40
Reel HS 400 / 395/60-185	395	180	60	185	145	20	14079		2x16	71
Reel HS 401 / 395/60-280	395	180	60	280	240	20	23303		2x16	71
Reel USR 395	395	175	36 - 100	280	120 - 300	20	11818 - 29546		1x32,5	85.4
Reel USR 435/56-485	435	125	56	485	445	20	60673		1x24	76
Reel KCS 500 (Type 057)	500	150	56	460	410	25	73000			
Reel HS 600 / 595/80-500	595	350	80	500	430	35	78190		1x40	99
Reel HS 601 / 595/80-500	595	250	80	500	430	35	98454		1x40	99
Reel USR 595	595	250	36 - 100	470	310 - 400	35	70978 - 91585		1x32,5	85.4
Reel KCS 710-ND (Type 070)	710	355	80	510	400	55	119000			
Reel HS 800 / 795/80-750	795	450	80	750	620	65	209155		2x40	100
Reel KCS 800 D2=500 mm	800	500	80	660	560	45	171530		2x40	100
Reel KCS 800-ND (Type 080)	800	400	80	510	400	55	151000			
Reel KCS 800-ND / 450	800	400	80	560	450	55	169000			
Reel KCS 900 N (Type 090)	900	450	80	690	560	65	267000			
Reel HS 1000/80-790	1000	500	80	790	650	70	382881		2 x 50	160
Reel KCS 1000-ND(Type 100)	1000	500	80	700	560	70	330000			
Reel HS 1200 / 1190/80-790	1190	600	80	790	650	70	539148		2x65	160

TECHNICAL DRAWING

Spools

