

18 BRAIDING REELS

Process reels for braiding wire

TOLERANCES

All dimensions, weights and loads stated are approximate values; tolerances and deviations which are customary for the industry remain reserved.



MATERIAL

POM = polyacetal

ABS = acrylonitrile-butadiene-styrene

PA6 = polyamide

Other materials and colours on request.

Further details regarding material can be found in our material data sheets.

Designation	Flange Ø	Barrel Ø	Central bore Ø	Width	Winding width	Flange thickness	Winding- volume	Central bore Ø tapered part	Drive- hole/pin	Drive- distance
	d1 [mm]	d2 [mm]	d3 [mm]	L1 [mm]	L2 [mm]	S [mm]	V [cm ³]	d4 [mm]	d5 [mm]	E1 [mm]
Reel WA 65/16-80	65.8	35.3	16.8	82.2	71.2	5.5	172			
Reel WA 65/16-82 S	67	34.5	16.5	81.8	69.2		179			
Reel WA 65/16-117 S	67	34.5	16.5	116.6	104		269			
Reel SPI 75/10-100 S	75	23	10	100	70		280			
Reel SPI 80/10-100 S	80	23	10	100	80		368			
Reel WA 80/16-86 S	80	34.5	16.5	85	70.5		288			

TECHNICAL DRAWING

Spools

