

11 REELS FOR STEEL CORD, BARE WIRE, STRANDED WIRE

Delivery spools for all kinds of wire, such as low alloy steels, hose wire, steel cord, bare wire, and stranded wire

SPECIAL REQUESTS

We can customize almost all models with your company logo subject to a minimum quantity. Special designs, e.g. additional bores or a slots in the barrel to insert the beginning of the wire or tape are available on request. Please contact us for details.

TOLERANCES

All dimensions, weights and loads stated are approximate values; tolerances and deviations which are customary for the industry remain reserved.

Important

Shrink-wrapped pallets of packages must not be stored in direct sunlight, as the heat build-up may cause the plastic to warp permanently. Shrink-wrapped pallets are the preferred mode of shipment for reels. All types can also be packed in sturdy corrugated cardboard boxes. On request, we also ship cardboard boxes on shrink-wrapped pallets. Overseas container shipping (20 feet or 40 feet) is also possible. Please ask for shipping quantities. Also possible in combined quantities.



MATERIAL

The material options for the reels are indicated as follows:

HIPS = high impact polystyrene

ABS = acrylonitrile-butadiene-styrene

PA6 = glass fibre reinforced polyamide

Further details and the available colours can be found in our material data sheets.

For the following reels, anthracite is the standard colour for HIPS and ABS.

Other colours are available. Further materials on request.

Designation	Flange Ø	Barrel Ø	Central bore Ø	Width	Winding width	Flange thickness	Winding-volume	Central bore Ø tapered part	Drive-hole/pin	Drive-distance
	d1 [mm]	d2 [mm]	d3 [mm]	L1 [mm]	L2 [mm]	S [mm]	V [cm³]	d4 [mm]	d5 [mm]	E1 [mm]
Reel US P 5	123.4	76.2	16.2	101.6	88.9	6.4	657			
Reel MA 125/16-37	125	90	16	37	30	3.5	177			
Reel RE 125	125	60	16	125	100	12.5	876			
Reel JP 3	130	80	20	110	90	10	742			
Reel KM 150	150	76	16	92	70	11	919			
Reel US P 4	152	89	16	110	90	10	1073			
Reel JP 5	160	90	20	114	90	12	1237			
Reel B 10/17 recessed	165	95	17	103	88	7.5	1257			
Reel B 10/17 smooth	165	95	17	103	88	7.5	1257			
Reel B 10/47 recessed	165	95	47	103	88	7.5	1257			
Reel BA 175/230	175	106	54	230	212	9	3228			
Reel BK 180/18-113	180	86	18	113	82	6.5	1610			
Reel AD 200	200	75	65	58	50	4	1350			
Reel AD 200/67,5	200	75	67.5	58	50	4	1350			
Reel B 20/46 smooth	200	100	46	115	100	7.5	2356			
Reel SJ 200	200	100	46	124	100	12	2356			

Designation	Flange Ø	Barrel Ø	Central bore Ø	Width	Winding width	Flange thickness	Winding- volume	Central bore Ø tapered part	Drive- hole/pin	Drive- distance
	d1 [mm]	d2 [mm]	d3 [mm]	L1 [mm]	L2 [mm]	S [mm]	V [cm ³]	d4 [mm]	d5 [mm]	E1 [mm]
Reel FR 200	202	110	32.5	180	160	10	3605			
Reel BP 60 ND	254	102	25.4 - 32.5	184	153	15.5	6502			
Reel B 60 recessed	255	117	17 - 33	166	151	7	6060			
Reel B 60 smooth	255	117	17 - 33	166	151	7	6060			
Reel B 260/36-190	260	122	36	190	152	9.5	6293			
Reel BK 280/22-173	280	138	22	173	126	9.5	5874			
Reel H 335/180-245	335	188	180	245	215	15	12982			

TECHNICAL DRAWING

Spools

